


# TMB-HI

## EM Brake (with inverted hub)

Types: 0.6, 1.2, 2.5, 5, 10, 20

[ EM: Electromagnet ]



[ Special Order ]

TMB		0.6HI	1.2HI	2.5HI	5HI	10HI	20HI
Static Torque [ft-lbs / N-m]		4.4 / 6	8.9 / 12	18 / 24	37 / 50	74 / 100	148 / 200
Coil (20°C)	Voltage [DC-V]	24					
	Current [A]	0.5	0.65	0.92	1.35	1.6	2.2
	Resistance [Ω]	48	37	26	18	15	11
	Wattage [W]	12	15	22	33	38	53
Armature	Pull-In Time [ms]	10	16	16	25	40	55
	Release Time [ms]	10	10	24	25	35	62
Torque Build-Up Time [ms]		42	46	51	56	78	95
Max Allowable Speed [rpm]		5000	5000	4500	4000	3600	3000
Moment of Inertia (J) [kg-cm <sup>2</sup> ]		0.75	2.5	7.8	23	72	248
Max Air Gap Until Adjustment [mm]		0.5	0.6	0.7	0.8	1.2	1.5
Total Energy Until Adjustment [J]		2.9 x 10 <sup>7</sup>	6.6 x 10 <sup>7</sup>	13 x 10 <sup>7</sup>	26 x 10 <sup>7</sup>	62 x 10 <sup>7</sup>	120 x 10 <sup>7</sup>
Total Energy Until Life [J]		13 x 10 <sup>7</sup>	25 x 10 <sup>7</sup>	49 x 10 <sup>7</sup>	88 x 10 <sup>7</sup>	170 x 10 <sup>7</sup>	320 x 10 <sup>7</sup>
Bore [mm]	dH7	12	15	20	25	30	40
Key Way [mm]	bE9	4	5	5	7	7	10
	t+0.15/-0	13.5	17	22	28	33	43.5
Dimensions [mm]	A	67	86	108	136	170	215
	B	26	32	40	50	65	80
	D+0.2/-0	35	45	52	65	80	107
	E	62	82	100	125	156	200
	F+0/-0.2	85	110	135	165	210	265
	G	75	98	122	150	190	240
	H	4.5	5.5	6.5	6.5	8.5	11
	L	28	31.5	36.5	41	47	56.5
	M	19.2	21.1	23.4	25.2	27.1	31.2
	N	13	11.5	11.5	11	7	6.5
	O	15	20	25	30	40	50
	P	1.8	2.1	2.4	2.4	2.7	3
S	0.2~0.3	0.2~0.3	0.2~0.3	0.2~0.3	0.3~0.4	0.4~0.5	
Weight [lbs / kg]		0.9 / 0.4	2.0 / 0.9	3.5 / 1.6	6.0 / 2.7	11 / 5	21 / 10

[ Included parts & accessories : shims, surge protector ]

[ 1 inch = 25.4 mm ]